$\begin{array}{c} \textbf{Understanding} \ \textbf{UL}^{\text{\tiny{B}}} \\ \textbf{Safety} \ \textbf{Standards} \ \textbf{for} \ \textbf{Medical} \ \textbf{Beds} \\ \end{array}$







What does UL Stand For?

UL stands for "Underwriters Laboratories". Underwriters Laboratories® is an independent product safety certification organization that has been testing products and writing safety standards for more than a century. UL evaluates more than 19,000 types of products, components, materials and systems annually with 21 billion UL Marks appearing on 72,000 manufacturers' products each year.

What does UL listed Mean?

When a device is UL-listed, this means that UL has tested the device, and it meets their requirements for safety – i.e., fire or shock hazard. In the last 20 years, the UL Safety Standard for Medical Beds has evolved from UL544 to UL2601 to UL60601. UL60601-1 is the General Requirements for Safety for Medical Electrical Equipment, which also concurs with IEC601-2-38.

What UL 60601 Requirements are There for Medical Beds and Why do They Matter?

 No Scissors or Crush Pinch Points within 200mm (Approx 7.9") of Bed Perimeter

The absence of pinch points reduces the risk of resident injury when a resident is lying on the bed, during articulation of the bed, or during transfer of a resident to or from the bed. Basic American beds are designed with recessed bed frames to comply with this requirement.



• Tip Stability Testing

Bed stability, critical in long term care settings, is a strong focus due to the high concern with resident movement and placement in a bed. The Zenith™ Z3, as all Basic American beds, was tested, loaded at the perimeter with castersturned to worst-case position, placed on an incline to test for stability, and passed.

Load Capacity Testing

A bed's weight capacity is tested at higher standards than those listed to ensure that the weight capacity claimed is worst-case scenario. The Zenith Z3 has a Certified 500 lb rating and was tested at twice that weight for UL approval. It is the superior frame on all Basic American beds that keeps our beds strong and long lasting.



• Rolling Clearance of 20mm (approx. 0.79") minimum for Transport

Rolling clearance of 20mm, which allows beds to travel easily over thresholds, is appropriate for long term care facilities in cases of emergency or routine transport.

• All Electronics have IPX4 Splash-proof Rating
Because bed systems are subject to resident
incidents and constant cleaning, it is critical that all
electrical components withstand normal wear and
maintenance. All Basic American beds have been
tested to ensure utmost safety for residents and staff.

For more information on UL and FDA Guidelines for Medical Beds, Basic American encourages you to review the FDA's <u>Hospital Bed Safety</u> page at http://www.fda.gov/cdrh/beds.



Specifications are subject to change without notice.
Basic American Medical Products and Zenith are registered trademarks, of
GF Health Products, Inc. UL and Underwriters Laboratories are registered
trademarks of Underwriters Laboratories Inc.
© 2009 GF Health Products, Inc. All rights reserved. GF0900153RevA09