

6810A-CLA/6810A-CSA: REPLACING YOUR VERSAMODE ™ DROP ARM CASTERS REPLACEMENT OPERATION INSTRUCTIONS

SAVE THESE INSTRUCTIONS FOR FUTURE USE

- ⚠ WARNING: Important! Read and understand these instructions before installing the casters. If the casters are not properly installed, personal injury and damage to the chair could result.
- ⚠ WARNING: If components are damaged or missing, contact your GF Health Products, Inc. authorized distributor immediately. DO NOT use substitute parts. Use only Lumex replacement parts. Non-Lumex replacement parts could cause personal injury and cause damage to the casters or chair.
- ⚠ WARNING: GF Health Products, Inc. assumes no responsibility for any damage or injury caused by improper assembly, installation or use of this product.

Tools Required: M6 open-ended wrench and Phillips-head screwdriver.

HOW TO REPLACE COMMODE CASTER(S)

Collect necessary tools and replacement caster(s).

- To remove the old caster(s), use screwdriver and wrench to loosen screw and gasket at base of caster. Once loosened, directly pull caster from frame.
- 2. Insert new caster wheel assembly into frame tube.
- 3. Align holes of the wheel with holes of frame and insert screw through hole.
- 4. Place gasket at end of screw.
- 5. Use screwdriver and wrench to tighten caster into leg until completely secure.
- 6. Repeat with any remaining casters as necessary.
- ⚠ CAUTION: It is important to always check your casters for proper performance and maintain them on a regular basis.
- ⚠ CAUTION: It is important to always check your casters and all components of the chair for proper function before every use.









